

Eine Wellenlänge voraus



50 Hz	P2 (kW)	P1 (kW)	 (min ⁻¹)	I _φ (A)				 Anzahl/mm ²	 (ml)	 3-fach SIC/SIC	 (mH ₂ O)	 (kg)			Q max (L/min)	H max (m)
				230 V	400 V								Höhe	Ø		
SPT 400R/W(S)	0,4	0,58	2850	3				H07RN-F 3x1,0	175	3-fach SIC/SIC	10	12/12,5	352	243	230	12
SPT 750 R/W(S)	0,75	1,15	2850	6,5				H07RN-F 3x1,0	175	3-fach SIC/SIC	10	16/16,5	377	279	350	18
SPT 1500R/W	1,5	2,32	2850	12				H07RN-F 3x1,5	250	3-fach SIC/SIC	10	19,3	446	313	630	21
SPT 400R/D	0,4	0,58	2850		0,9			H07RN-F 4x1,0	175	3-fach SIC/SIC	10	19,3	352	243	230	12
SPT 750R/D	0,75	1,15	2850		1,8			H07RN-F 4x1,0	175	3-fach SIC/SIC	10	12,5	377	279	350	18
SPT 1500R/D	1,5	2,32	2850		4,0			H07RN-F 4x1,0	250	3-fach SIC/SIC	10	19,3	446	313	630	21
SPT 370 W(S)	0,4	0,58	2850	3				H07RN-F 3x1,0	200	3-fach SIC/SIC	10	13/13,5	310	186	240	10
SPT 750 W(S)	0,75	1,15	2850	5,4				H07RN-F 3x1,0	200	3-fach SIC/SIC	10	15/15,5	335	186	320	15,8
SPT 1500 NW	1,5	2,32	2850	12				H07RN-F 3x1,5	200	3-fach SIC/SIC	10	24	525	219,5	480	19
SPT 370 D	0,4	0,58	2850		3,5			H07RN-F 4x1,0	200	3-fach SIC/SIC	10	15	310	186	240	10
SPT 750 D	0,75	1,15	2850		2			H07RN-F 4x1,0	200	3-fach SIC/SIC	10	15	335	186	320	15,8
SPT 1500 D	1,5	2,32	2850		3,5			H07RN-F 4x1,0	250	3-fach SIC/SIC	10	24	525	219,5	480	19
FSP 400 W	0,4	0,58	2850	3				H07RN-F 3x1,0	250	3-fach SIC/SIC	10	11	309,5	259	125	12
SPR(E) 370 W	0,4	0,58	2850	3				H07RN-F 3x1,0	200	3-fach CA/CE+SIC	10	12	320	183,5	230	11
SPR(E) 750 W	0,75	1,15	2850	5,4				H07RN-F 3x1,0	200	3-fach CA/CE+SIC	10	15	347	183,5	320	15,8
SPR 750 D	0,75	1,15	2850		2			H07RN-F 4x1,0	200	3-fach SIC/SIC	10	11	337,5	214	320	15,8
SPT 215/315	1,5	2,17	2850		3,5			H07RN-F 4x1,5	600	3-fach SIC/SIC	25	14	517	235	450/666	22/14,5
SPT 222/322	2,2	3,15	2850		5			H07RN-F 4x1,5	600	3-fach SIC/SIC	25	37	517	235	450/833	26/21
SPT 237-437	3,7	4,9	2850		7,7			H07RN-F 4x2,5	1000	3-fach SIC/SIC	25	65/65/66	628	283	483/916/1500	34/29/18
SPT 355-455	5,5	6,9	2850		11			H07RN-F 4x3,5	1000	3-fach SIC/SIC	25	84/85	671	306	1166/1750	32/23
SPT 475-675	7,5	9,2	2850		15			H07RN-F 4x3,5	1000	3-fach SIC/SIC	25	114	764	330	1400/2080	40/31
SPT 4110-6110	11	13,5	2850		22			H07RN-F 4x5,5	800	3-fach SIC/SIC	25	140/143	807	373	1440/2450	48,5/32
SPT 4150-6150	15	18,5	2850		30			H07RN-F 4x5,5	800	3-fach SIC/SIC	25	153/156	1295	373	1440/2600	32/56
SPT 8220N+H	22	26,5	2850		43			H07RN-F 7x6+2x1,5		3-fach SIC/SIC	25	410	1295	580	6500/5500	25/35
KSC(E) 237-437	3,7	4,9	2850		7,7			H07RN-F 4x2,5	1000	3-fach SIC/SIC	25	45	605	300	483/916/1500	34/29/18
KSC(E) 355-455	5,5	6,9	2850		11,4			H07RN-F 4x3,5	1000	3-fach SIC/SIC	25	50	645	300	1166/1750	32/23
SPT 15-1	1,5	2,3	2850	13				H07RN-F 3x1,5		2-fach SIC/SIC	10	26	492	222	400	14
SPT 15-3	1,5	2,3	2850		3,8			H07RN-F 4x1,5		2-fach SIC/SIC	10	26	492	222	400	14
SHL 422-622	22	26,5	2850					H07RN-F 7x6+2x1,5	6500	3-fach SIC/SIC	25	365/370	1374	240	2166/3333	68/50
SHL 430-630	30	35,5	2850					H07RN-F 7x6+2x1,5	6500	3-fach SIC/SIC	25	375/380	1434	250	2833/3666	78/56

Eine Wellenlänge voraus



50 Hz	P2 (kW)	P1 (kW)	 (min ⁻¹)	 (A)		 Anzahl/mm ²		 (ml)		 (mH ₂ O)	 (kg)			Q max (L/min)	H max (m)
				230 V	400 V							Höhe	Ø		
SPT 80R	4	5,3	1450		9,9						113	765	350	1650	14,8
SPT 100R	6	7,5	1450		13,4						156	848	415	2500	16,9
SPT 150R	9	11	1450		19						184	869	434	2850	21,5
ASP 337	3,7	4,9	1480		7,9						130	820	410	1500	14
ASP 455	5,5	6,9	1480		11,5						150	820	410	2000	17
ASP 475	7,5	9,2	1480		15,2						180	840	410	2400	19
ASP 6110	11	13,5	1480		22,7						245	1100	485	4000	22
ASP 6150	15	18,5	1480		29,9						265	1100	485	3100	34
ASP 8220	22	26,5	1480		45,5						410	1325	543	5200	30
KPS 550 W(S)	0,55	0,8	2850	3,58							11/11,5	357	178	250	10,9
KPS 750 W(S)	0,75	1,15	2850	4,78							14/14,5	407	178	325	14
KPS 1100 W(S)	1,1	1,65	2850	7,21							16/16,5	407	178	375	16,1
KPS 550 D	0,55	0,8	2850		1,33						11	407	178	250	10,9
KPS 750 D	0,75	1,15	2850		2,07						14	407	178	325	14
KPS 1100 D	1,1	1,65	2850		2,48						14	407	178	375	16,1
KPS 1500 D	1,5	1,65	2850		3,31						16	407	178	520	20,6
KPV 550 W(S)	0,55	0,8	2850	3,58							10/11,5	403	193	260	9,1
KPV 750 W(S)	0,75	1,15	2850	4,78							13/13,5	486	198	400	7,7
KPV 1100 W(S)	1,1	1,65	2850	7,21							14/14,5	486	198	450	9,1
KPV 550 D	0,55	0,8	2850		1,33						10	403	193	260	9,1
KPV 750 D	0,75	1,15	2850		2,07						13	486	198	400	7,7
KPV 1100 D	1,1	1,65	2850		2,48						13	486	198	450	9,1
KPV 1500 D	1,5	2,32	2850		3,31						14	486	198	550	11
AV(E) 204 S(A)	0,40	0,58	2850	4							13/13,5	381	223	320	8
AV(E) 208 S(A)	0,75	1,15	2850	6							18/18,5	411	223	460	12,5
AV(E) 215 S	1,5	1,65	2850	11,3							33	570	390	650	17,5
AV(E) 315 S	1,5	1,65	2850	11,3							33	570	390	650	17,5
AV(E) 322	2,2	3,15	2850		5,2						34	590	458	750	19,5
AV(E) 437	3,7	4,9	2850		8,6						56	633	458	1200	23,5

[illegible]